



## FLEXAMAT PLUS UV-T - ACCESS ROAD ARMORING

SUBGRADE THICKNESS OF CRUSHED STONE		
SITE SOIL TYPE	LIGHT LOAD VEHICLES: CARS/PICKUP TRUCKS	HEAVY LOAD VEHICLES: LARGE TRUCKS, RV'S, DELIVERY VEHICLES
GRAVEL AND SAND, COURSE WELL DRAINED SOILS	BASE: 3.5-7.5" OF CRUSHED STONE	BASE: 7.5" OF CRUSHED STONE
SILTY SOILS, FINE GRAIN SOILS, POOR DRAINAGE	BASE: 7.5" OF CRUSHED STONE	BASE: 9.5" OF CRUSHED STONE
CLAY SOILS FINE TO VERY FINE	BASE: 6-9.5" OF CRUSHED STONE	BASE: 10" OF CRUSHED STONE

\*ROLLS AVAILABLE IN MULTIPLE WIDTHS: 4', 5.5', 8', 10', 12', AND 16'. FOR ARMORING WIDER THAN 16', A 15.5' ROLL WITH A 6" PLUS EXTENSION AND A 12" GEOGRID EXTENSION FOR ABUTMENTS SHALL BE USED.

## MOTZ ENTERPRISES, INC.

Flexamat  
(513)772-6689  
Info@Flexamat.com  
Flexamat.com

