



FLEXAMAT INFORMATION

Manufacturer: Motz Enterprises Inc.
 Product Name: Flexamat
 Address: 3153 Madison Road
 Cincinnati, Ohio 45209
 Telephone: 513-772-7645
 Email: Info@Flexamat
 Website: www.Flexamat.com

CONSTRUCTION NOTES:

1. GRADE CHANNEL SO THAT WATER WILL FLOW DOWN THE CENTER OF THE CHANNEL AND BE CONTAINED TO THE CHANNEL. ALL SUBGRADE SURFACES PREPARED FOR PLACEMENT OF MATS SHALL BE SMOOTH AND FREE OF ALL ROCKS, STICKS, ROOTS, OTHER PROTRUSIONS, OR DEBRIS OF ANY KIND. THE PREPARED SURFACE SHALL PROVIDE A FIRM UNYIELDING FOUNDATION FOR THE MATS.
2. APPLY SEED DIRECTLY TO THE PREPARED SOIL PRIOR TO FLEXAMAT INSTALLATION. USE SEED PER PROJECT SPECIFICATIONS.
3. INSTALL FLEXAMAT ROLLS. AVAILABLE WIDTHS ARE 4', 5.5' 8', 10', 12' & 16'. AVAILABLE IN CUSTOM LENGTHS. SEE CHANNEL DETAIL WIDER THAN 16' FOR ADDRESSING LONGITUDINAL SEAMS.
4. AT THE TOP OF THE CHANNEL THE AROUND THE INLET ENSURE A FLUSH TRANSITION FROM CURB INLET. ANCHOR WITH #3 REBAR - 18" "U" ANCHORS IN 2' INCREMENTS AROUND THE INLET.

FLEXAMAT® CURB INLET DETAIL

